

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number
WO 2005/091389 A1

(51) International Patent Classification⁷: **H01L 33/00**

[JP/JP]; c/o Showa Denko K.K., 5-1, Yawata Kaigan dori, Ichihara-shi, Chiba, 2900067 (JP).

(21) International Application Number:
PCT/JP2005/005439

(74) Agents: **AOKI, Atsushi** et al.; A. AOKI, ISHIDA & ASSOCIATES, Toranomom 37 Mori Bldg., 5-1, Toranomom 3-chome, Minato-ku, Tokyo 1058423 (JP).

(22) International Filing Date: 17 March 2005 (17.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-081286 19 March 2004 (19.03.2004) JP
60/560,269 8 April 2004 (08.04.2004) US

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (for all designated States except US): **SHOWA DENKO K.K.** [JP/JP]; 13-9, Shibadaimon 1-chome, Minato-ku, Tokyo, 1058518 (JP).


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KUSUNOKI, Katsuki**

[Continued on next page]

(54) Title: COMPOUND SEMICONDUCTOR LIGHT-EMITTING DEVICE AND PRODUCTION METHOD THEREOF



(57) Abstract: An object of the present invention is to provide a compound semiconductor light-emitting device having side surfaces of large surface area to improve the efficiency for outwardly transmitting the emitted light. Another object of the present invention is to provide a technology capable of easily forming the side surfaces with large surface area without using a cutting tool and without the need of taking a trouble to impart mechanical damage. The inventive compound semiconductor light-emitting device has a light-emitting layer, on a substrate, wherein at least a part of a substrate portion of the device side surface has recessed portions in a side direction of the device. The inventive method of producing compound semiconductor light-emitting device comprises the steps of: (a) forming a compound semiconductor layer including a light-emitting layer of an n-type or p-type compound semiconductor on a wafer that serves

as a substrate, (b) arranging a negative electrode and a positive electrode at predetermined positions for passing a drive current through the light-emitting layer, (c) forming a separation zone for separating the individual light-emitting devices, (d) perforating many small holes linearly in the wafer that serves as the substrate along the separation zone, and (e) dividing the wafer into individual light-emitting devices along the separation zone.

WO 2005/091389 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*